August 17, 2006

Reply to Office Action of:

May 17, 2006

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

MAT-8014US

Listing of Claims:

- (Currently Amended) A method of transmitting data packets, said method comprising the steps of:
- (a) generating a fixed pattern comprising 'm' words ('m' is an integer greater than 0);
- (b) generating variable, non-random patterns of predetermined bit structure, each pattern comprising 'n' words ('n' is an integer greater than 1);
- (c) generating sync patterns comprising 'q' words ('q' = m + n), each of the sync patterns formed by combining the fixed pattern and one of the variable patterns;
- (d) adding one of said sync patterns to each of said data packets in a data stream, wherein consecutive ones of said data packets each have added respectively different variable patterns.

wherein the variable pattern comprises a plurality of words, and the variable patterns are made by changing an order of the words.

- 2. (Cancelled)
- 3. (Original) The method as defined in Claim 1, wherein the fixed pattern comprises three words.

Application No.: Amendment Dated: Reply to Office Action of: 09/646,665 August 17, 2006 May 17, 2006

- 4. (Original) The method as defined in Claim 3, wherein the three words includes 'eb', 'cb' and 'aa', expressed in a hexadecimal notation.
- 5. (Original) The method as defined in Claim 1, wherein the variable pattern comprises five words.
- 6. (Original) The method as defined in Claim 5, wherein the five words includes '4c', 'ea', 'cd', '7a' and '81', expressed in a hexadecimal notation.
- 7. (Previously Presented) The method as defined in Claim 1, wherein the variable patterns are '4ceacd7a81' and 'cd7aea814c' expressed in a hexadecimal notation.

8. - 11. (Cancelled)

- 12. (Original) A method of receiving a packet data transmitted by the method defined in Claim 1, said method including a step of detecting a sync.
- 13. (Original) A method of receiving a packet data transmitted by the method defined in Claim 1, said method including the steps of:
- (a) detecting a sync for examining both of a fixed pattern and a variable pattern of a data received; and
 - (b) securing a sync for examining only the fixed pattern,

wherein said step (a) processes the data until the sync is secured, and said step (b) processes the data after the sync is secured.

14. (Currently Amended) A packet data transmitting apparatus for transmitting data packets, said transmitting apparatus comprising:

MAT-8014US

Application No.:

09/646,665

Amendment Dated:

August 17, 2006

Reply to Office Action of:

May 17, 2006

(a) means for generating a fixed pattern comprising 'm' words ('m' is an integer greater than 0);

- (b) means for generating variable, non-random patterns of predetermined bit structure, each pattern comprising 'n' words ('n' is an integer greater than 1);
- (c) means for generating sync patterns comprising 'q' words ('q' = m + n), each of the sync patterns formed by combining the fixed pattern and one of the variable patterns; and
- (d) means for adding one of said sync patterns to each of said packets in a data stream, wherein consecutive ones of said data packets each have added respectively different variable patterns.

wherein the variable pattern comprises a plurality of words, and the variable patterns are made by changing an order of the words.

- 15. (Previously Presented) A packet data receiving apparatus for receiving the packet data transmitted by the method defined in Claim 1, said receiving apparatus comprising:
- (a) means for detecting a sync for examining both of a fixed pattern and a variable pattern of a data received; and
 - (b) means for securing a sync for examining only the fixed pattern,

wherein said means defined in (a) processes the data until the sync is secured, and said means defined in (b) processes the data after the sync is secured.

09/646,665 August 17, 2006

Reply to Office Action of:

May 17, 2006

16. (Previously Presented) A method as defined in Claim 1, wherein the packet data comprises a plurality of blocks, and the blocks include 's' words having a block header of 'm' words, said method further comprising the step of:

adding a transmission header of 's \times k' words (k is a natural number),

wherein the transmission header is divided into 'k' pieces of blocks at intervals of every 's' words, each block of said 'k' pieces of blocks includes the fixed pattern of 'm' words at a top thereof, the fixed pattern employs a pattern other than patterns used in the block header.

- 17. (New) A method of transmitting data packets, said method comprising the steps of:
- (a) generating a fixed pattern comprising 'm' words ('m' is an integer greater than 0);
- (b) generating variable, non-random patterns of predetermined bit structure, each pattern comprising 'n' words ('n' is an integer greater than 1);
- (c) generating sync patterns comprising 'q' words ('q' = m + n), each of the sync patterns formed by combining the fixed pattern and one of the variable patterns;
- (d) adding one of said sync patterns to each of said data packets in a data stream, wherein consecutive ones of said data packets each have added respectively different variable patterns

wherein the variable patterns are '4cead7a81' and 'cd7aea814c' expressed in a hexadecimal notation.

09/646,665 August 17, 2006

Reply to Office Action of:

May 17, 2006

- 18. (New) A method as defined in Claim 17, wherein the fixed pattern comprises three words.
- 19. (New) A method as defined in Claim 18, wherein the three words includes 'eb', 'cb' and 'aa', expressed in a hexadecimal notation.
- 20. (New) a method of receiving a packet data transmitted by the method defined in Claim 17, said method including a step of detecting a sync.
- 21. (New) A method of receiving a packet data transmitted by the method defined in Claim 17, said method including the steps of:
- (a) detecting a sync for examining both of a fixed pattern and a variable pattern of a data received; and
 - (b) securing a sync for examining only the fixed pattern,

wherein said step (a) processes the data until the sync is secured, and said step (b) processes the data after the sync is secured.

- 22. (New) A packet data transmitting apparatus for transmitting data packets, said transmitting apparatus comprising:
- (a) means for generating a fixed pattern comprising 'm' words ('m' is an integer greater than 0);
- (b) means for generating variable, non-random patterns of predetermined bit structure, each pattern comprising 'n' words ('n' is an integer greater than 1);

09/646,665 August 17, 2006

Reply to Office Action of:

May 17, 2006

- (c) means for generating sync patterns comprising 'q' words ('q' = m + n), each of the sync patterns formed by combining the fixed pattern and one of the variable patterns; and
- (d) means for adding one of said sync patterns to each of said packets in a data stream, wherein consecutive ones of said data packets each have added respectively different variable patterns,

wherein the variable patterns are '4ceacd7a81' and 'cd7aea814c' expressed in a hexadecimal notation.

- 23. (New) A packet data receiving apparatus for receiving the packet data transmitted by the method defined in Claim 17, said receiving apparatus comprising:
- (a) means for detecting a sync for examining both of a fixed pattern and a variable pattern of a data received; and
 - (b) means for securing a sync for examining only the fixed pattern,

wherein said means defined in (a) processes the data until the sync is secured, and said means defined in (b) processes the data after the sync is secured.

24. (New) A method as defined in Claim 17, wherein the packet data comprises a plurality of blocks, and the blocks includes 's' words having a block header of 'm' words, said method further comprising the step of:

adding a transmission header of 's X k' words (k is a natural number),

09/646,665 August 17, 2006

Reply to Office Action of:

May 17, 2006

wherein the transmission header is divided into 'k' pieces of blocks at intervals of every 's' words, each block includes the fixed pattern of 'm' words at a top thereof, the fixed pattern employs a pattern other than patterns used in the block header.

- 25. (New) A method of transmitting data packets, said method comprising the steps of:
- (a) generating a fixed pattern comprising 'm' words ('m' is an integer greater than 0);
- (b) generating variable, non-random patterns of predetermined bit structure, each pattern comprising 'n' words ('n' is an integer greater than 1);
- (c) generating sync patterns comprising 'q' words ('q' = m + n), each of the sync patterns formed by combining the fixed pattern and one of the variable patterns;
- (d) adding one of said sync patterns to each of said data packets in a data stream, wherein consecutive ones of said data packets each have added respectively different variable patterns,

wherein the variable patterns are two patterns.

- 26. (New) The method as defined in Claim 25, wherein the variable pattern comprises a plurality of words, and the variable patterns are made by changing an order of the words.
- 27. (New) The method as defined in Claim 25, wherein the fixed pattern comprises three words.

09/646,665 August 17, 2006

Reply to Office Action of:

May 17, 2006

- 28. (New) The method as defined in Claim 27, wherein the three words includes 'eb', 'cb' and 'àa', expressed in a hexadecimal notation.
- 29. (New) The method as defined in Claim 25, wherein the variable pattern comprises five words.
- 30. (New) The method as defined in Claim 29, wherein the five words includes '4c', 'ea', 'cd', '7a' and '81', expressed in a hexadecimal notation.
- 31. (New) The method as defined in Claim 25, wherein the variable patterns are '4ceacd7a81' and 'cd7aea814c' expressed in a hexadecimal notation.
- 32. (New) A method of receiving a packet data transmitted by the method defined in Claim 25, said method including a step of detecting a sync.
- 33. (New) A method of receiving a packet data transmitted by the method defined in Claim 25, said method including the steps of:
- (a) detecting a sync for examining both of a fixed pattern and a variable pattern of a data received; and
 - (b) securing a sync for examining only the fixed pattern,

wherein said step (a) processes the data until the sync is secured, and said step (b) processes the data after the sync is secured.

- 34. (New) A packet data transmitting apparatus for transmitting data packets, said transmitting apparatus comprising:
- (a) means for generating a fixed pattern comprising 'm' words ('m' is an integer greater than 0);

09/646,665 August 17, 2006

Reply to Office Action of: May 17, 2006

(b) means for generating variable, non-random patterns of predetermined bit structure, each pattern comprising 'n' words ('n' is an integer greater than 1);

- (c) means for generating sync patterns comprising q' words q' = m + n, each of the sync patterns formed by combining the fixed pattern and one of the variable patterns; and
- (d) means for adding one of said sync patterns to each of said packets in a data stream, wherein consecutive ones of said data packets each have added respectively different variable patterns,

wherein the variable patterns are two patterns.

- 35. (New) A packet data receiving apparatus for receiving the packet data transmitted by the method defined in Claim 25, said receiving apparatus comprising:
- (a) means for detecting a sync for examining both of a fixed pattern and a variable pattern of a data received; and
 - (b) means for securing a sync for examining only the fixed pattern,

wherein said means defined in (a) processes the data until the sync is secured, and said means defined in (b) processes the data after the sync is secured.

36. (New) A method as defined in Claim 25, wherein the packet data comprises a plurality of blocks, and the blocks includes 's' words having a block header of 'm' words, said method further comprising the step of

MAT-8014US

Application No.: Amendment Dated: 09/646,665 August 17, 2006

Reply to Office Action of: May 17, 2006

adding a transmission header of 's X k' words (k is a natural number),

wherein the transmission header is divided into 'k' pieces of blocks at intervals of every 's' words, each block includes the fixed pattern of 'm' words at a top thereof, the fixed pattern employs a pattern other than patterns used in the block header.